





PERMALOC CORPORATION
13505 BARRY ST
HOLLAND, MI 49424
TOLL FREE: 1-800-356-9660
PHONE: (616) 399-9600
FAX: (616) 399-9770
www.permaloc.com

☒ SELECT DESIRED SIZE (IN 8' (2.44 M) LENGTHS WITH .21" (5.33 MM) THICK EXPOSED TOP LIP):

- ☐ 1" X 2.25" (25 MM X 57 MM)
- ☐ 1.5" X 2.25" (38 MM X 57 MM)
- ☐ 2" X 2.25" (51 MM X 57 MM)
- ☐ 2.5" X 2.25" (64 MM X 57 MM)
- ☐ 3" X 3" (76 MM X 76 MM)
- ☐ 4" X 3" (102 MM X 76 MM)
- ☐ 5" X 3" (127 MM X 76 MM)
- ☐ 6" X 3" (152 MM X 76 MM)

☒ SELECT DESIRED FINISH:

- ☐ MF - MILL FINISH-NATURAL ALUMINUM
- ☐ BL - BLACK DURAFLEX-ELECTROSTATICALLY APPLIED BAKED ON PAINT, MEETS AAMA 2603




NOTES:

- 8'-0" (2.44 M) SECTIONS CONNECTED WITH 4" (102 MM) SLIDING CONNECTOR.
- MAINTAIN 3/8" (9.5 MM) GAP BETWEEN SECTIONS TO ALLOW FOR PRODUCT EXPANSION IN EXTREME TEMPERATURES.
- CORNERS: NOTCH BASE ONLY AND FORM A CONTINUOUS CORNER.
- PERMALOC ASPHALTEdge AS MANUFACTURED BY PERMALOC CORPORATION.

NOTES:

- INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- DO NOT SCALE DRAWING.
- THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
- ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
- CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 006-055



ASPHALTEdge ALUMINUM ASPHALT RESTRAINT

ASPHALT RUNNING TRACK RESTRAINING SINGLE COURSE OF ASPHALT OVER COMPACT GRAVEL
BASE CAD FILES AE-1